

MULTIPLE CONNECTORS



A range of male and female nylon multiple connectors, using standard 6.3mm spade terminals for securely joining cables from 1.0mm² to 2.5mm².

V344	1 way Nylon Connector (Male)
V345	1 way Nylon Connector (Female)
V346	2 way Nylon Connector (Male)
V347	2 way Nylon Connector (Female)
V348	3 way Nylon Connector (Male)
V349	3 way Nylon Connector (Female)
V350	4 way Nylon Connector (Male)
V351	4 way Nylon Connector (Female)

SUPERSEAL CONNECTORS



A top quality range of IP67 waterproof, male and female superseal connectors, for securely joining cables with cross sections from 0.5mm² to 1.5mm². The connectors come complete with terminals and seals. (5 and 6 way connectors also available).

V352	1 way Superseal Connector (Male)
V353	1 way Superseal Connector (Female)
V354	2 way Superseal Connector (Male)
V355	2 way Superseal Connector (Female)
V356	3 way Superseal Connector (Male)
V357	3 way Superseal Connector (Female)
V358	4 way Superseal Connector (Male)
V359	4 way Superseal Connector (Female)

RELAYS



Standard 1" square cube Mini ISO Relays are used extensively in the automobile industry as remote control electrical switches, allowing a small current flow circuit to control a higher current power circuit. Occasionally, diodes or resistors may be incorporated in the relay to avoid voltage spikes which can damage solid state devices. Semloh Electrics stock a wide range of Normally Open and Changeover Relays, with 6.3mm blade terminals, and the most popular formats are listed below. Other types are available on request.

Semloh Code	Voltage	Current Rating	Pin Layout	Internal Circuit	Relay Description
V337	12v	30A			A 4 Pin Normally Open 12v 30A Mini ISO Relay with detachable bracket.
V338	12v	30A			A 5 Pin Changeover 12v 30A Mini ISO Relay with detachable bracket.
V339	12v	40A			A 5 Pin Changeover 12v 40A Mini ISO Relay with moulded integral bracket
V340	12v	40A			A 5 Pin Changeover 12v 40A Mini ISO Relay with detachable bracket, and a diode fitted across the coil for voltage spike suppression.
V341	12v	40A			A 5 Pin Changeover 12v 40A Mini ISO Relay with no bracket, and a resistor fitted across the coil for voltage spike suppression.
V342	24v	20/30A			A 5 Pin Changeover 24v 20/30A Mini ISO Relay with detachable bracket
V343	Relay Holder			A standard relay holder with mounting hole and grooved sides which enable multiple holders to be connected together, or matching blade fuse holders to be added. Accepts up to 5 x 6.3mm or 4 x 2.8mm female spade connectors.	