

PROTECTIVE SHEATHING



An essential range of lead free, flexible black PVC tubular sleeving, ideal for the protection of wires and harnesses, or for bundling cables together. The PVC sleeving offers excellent chemical resistance to oil, petrol and water, high electrical insulation resistance, and has a wide working temperature range, from -25°C to +105°C.

PVC SLEEVING

for HARNESS and WIRE PROTECTION

Semloh Code	Internal Diameter (mm)	Wall Thickness (mm)	Coil Length (m)
V210	4.0	0.5	100m
V211	5.0	0.5	100m
V212	6.0	0.5	100m
V213	8.0	0.5	100m
V214	10.0	0.5	100m
V215	12.0	0.5	100m
V216	14.0	0.5	100m
V217	16.0	0.5	100m
V218	20.0	1.0	50m
V219	25.0	1.0	50m



This low density, halogen free, black polythene spiral binding offers a simple and fast method of bundling, binding and protecting cable looms, whilst at the same time allowing wires to be brought from the harness. It has an operating temperature range from -50°C to +85°C

POLYTHENE SPIRAL BINDING

for HARNESS and WIRE PROTECTION

Semloh Code	Nominal Size (mm)	Capacity (mm)	Internal Diameter (mm)	Coil Length (m)
V220	3.0	1.5 - 7.0	1.5	25m
V221	6.0	5.0 - 20.0	4.0	25m
V222	12.0	10.0 - 40.0	9.0	25m
V223	22.0	25.0 - 100.0	19.0	25m



A flame retardant, non adhesive, black PVC harness tape which is ideal for wrapping harnesses and wiring looms to protect them against abrasion, and offer extra insulation. The tape is 0.13mm thick, and has a working temperature range from 0°C to +90°C.

PVC NON-ADHESIVE HARNESS TAPE - Sold in packs of 10

Semloh Code	Tape Width (mm)	Colour	Roll Length (m)
V224	19	Black	20m
V225	25	Black	20m



A high quality, water and UV resistant, self-amalgamating resin tape, which is ideal for permanently waterproofing electrical cables and cable joints. Can also be used for fast, temporary repairs to hoses and water pipes. The tape is 0.5mm thick, and has a working temperature range from -30°C to +100°C.

SELF AMALGAMATING TAPE - Sold in packs of 10

Semloh Code	Tape Width (mm)	Colour	Roll Length (m)
V226	19	Black	10m
V227	25	Black	10m



A range of strong, flame retardant PVC self adhesive tapes suitable for general electrical insulation work, certified to BS3924. Its low cost makes this tape ideal also for bundling cables, tagging and colour coding as well as offering protection against abrasion. The tape has a working temperature range from 0°C to +70°C.

PVC ADHESIVE INSULATING TAPE - Sold in packs of 10

Semloh Code (use Suffix)	Normal Size (mm)	Colours Available	Roll Length (m)
V228	19mm wide x 0.15mm thick	Black(B), Red(R), Blue(U), Green(G), Yellow(Y), White(W), Brown(N), Grey(S) and Earth(E)	20m
V229	19mm wide x 0.18mm thick	Black	33m